

Certificate of
constancy of performance
0620-CPR-44024/19



Issued 2020-03-04 Replaces 0620-CPR-44024/18
First issued 2007-12-01 Page 1 of 2

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Aluminium lighting columns

Intended for use as road lighting columns for circulation areas
whereby the scope of construction product(s) is listed on page 2 of this certificate

placed on the market under the name or trademark of

Nedal Aluminium b.v.

and produced in the manufacturing plant

Utrecht

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 40-6:2002

under system 1 for the performances set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product**.

This certificate was first issued on 1 December 2007 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Ron Scheepers
Managing director

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

Kiwa Nederland B.V.
Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
info@kiwa.nl
www.kiwa.nl

Manufacturer
Nedal Aluminium b.v.
Groenewoudsedijk 1
3528 BG UTRECHT
Postbus 2020
3500 GA UTRECHT
Tel. 030-2925711
www.nedal.nl

Manufacturing plant
Nedal Aluminium b.v.
Groenewoudsedijk 1
3528 BG UTRECHT
Postbus 2020
3500 GA UTRECHT
Tel. 030-2925711
www.nedal.nl

SCOPE

Construction products

Aluminium lighting columns intended for use as road lighting columns for circulation areas according to EN 40-6: 2002 annex ZA.1 as indicated in the table below and for which at least one of the essential characteristics is declared as specified in the paragraph below.

The aluminium lighting columns may be:

- 1) Stepped, conical or cylindrical aluminium without or with single or double bracket;
- 2) With root section and or flange plate;
- 3) Equipped with 0 or more doors. The doors can be with the dimensions as be given in EN 40-6 and equipped with expanded inner reinforcement tube (reinforced door opening according to EN40-3-3 type 5);
- 4) installed with ALC MK3 Hinge above door with an maximum base capacity of 25,3 kN and a maximum Hinge capacity of 13,6 kN.

Product name	Description	Types
Boulevard	Conical straight Column	universal (straight) extension spigot single extension spigot multiple extension spigot
Avenue	Stepped straight Column	universal (straight) extension spigot single extension spigot multiple extension spigot
Faubourg	Cylindrical straight Column	universal (straight) extension spigot single extension spigot multiple extension spigot
Plaza	Conical Column with bracket (Conical hockeystick column)	standard conical bent model
Promenade	Stepped Column with bracket (Stepped hockeystick column)	
Special	Combination of above mentioned types, satisfying EN40 requirements	
Hinged columns	Seamless conical and stepped columns with ALC 3 MK 3 Hinge installed	

Essential characteristics**Resistance to horizontal loads**

The aluminium lighting columns within the scope of this certificate are designed to sustain safely the horizontal loads specified in EN 40-3-1 which is verified by calculation in accordance with EN 40-3-3.

Performance under vehicle impact (passive safety according to EN 12767)

For the aluminium lighting columns which fall within the range of the table below the performance class (passive safety code) is determined.

These aluminium lighting columns may be:

- 1) Stepped, conical or cylindrical aluminium without or with single or double bracket;
- 2) With root section (no flange plate) except when indicated otherwise;
- 3) Equipped with 0 or more doors. The doors can be with the dimensions as be given in EN 40-6 and equipped with expanded inner reinforcement tube (reinforced door opening according to EN40-3-3 type 5) except when indicated otherwise;
- 4) installed with ALC MK3 Hinge above door with an maximum base capacity of 25.26 kN and a maximum Hinge capacity of 13.6 kN.

Passive safety code EN 12767: 2019	Passive safety code EN 12767: 2007	Range light source height [m]	Max. bracket projection [m] ²	Max. bending capacity at ground level [kNm]	Backfill type / special installations	Other characteristics
50-NE-B-S-SE-MD-0 70-NE-B-S-SE-MD-0 100-NE-B-S-SE-MD-0	100-NE-3	2,0 - 5,4	1,3	7,46	S	
50-NE-B-X-SE-MD-0 70-NE-B-X-SE-MD-0 100-NE-B-X-SE-MD-0	70-NE-3 100-NE-3	2,0 – 15,0	2,0	29,91	X	With shear-off construction
100-NE-C-S-SE-MD-0	100-NE-2	2,0 – 12,4	1,5	18,70	S	
50-NE-C-R-SE-MD-NR 70-NE-C-R-SE-MD-NR 100-NE-C-R-SE-MD-NR	100-NE-2	2,0 – 18,1	1,5	29,91	S	Fixed flange plate with break bolts
50-NE-C-R-SE-MD-0 70-NE-C-R-SE-MD-0 100-NE-C-R-SE-MD-0	70-NE-2 100-NE-2	2,0 – 9,0	0,6	9,27	R - Installed 200 mm below ground level on rigid base	
100-NE-D-S-SE-MD-NR	100-NE-1	2,0 – 10,0	1,3	33,56	S	With elongated inner tube below ground level
100-LE-C-S-SE-BD-0	100-LE-3	10	1,3	18,70	S – fixed at least 1.7 m below ground level	Special elongated inner tube above ground level
100-LE-D-S-SE-BD-0	100-LE-2	8 – 12,4	1,3	18,70	S – fixed at least 1.7 m below ground level	Special elongated inner tube above ground level